

NEW ZEALAND STANDARD

METHODS OF TESTING SOILS
FOR CIVIL ENGINEERING
PURPOSES

Part 4
Soil compaction tests

4.2
DETERMINATION OF THE MINIMUM AND MAXIMUM DRY
DENSITIES AND RELATIVE DENSITY OF A COHESIONLESS SOIL

TEST 4.2.3
Relative density

4.2.3.1

Scope

This method determines the relative density of a soil with respect to the loosest and densest states at which it can be placed by the laboratory procedures specified in this Standard.

4.2.3.2

Related documents

The provisions of Part 1 of this Standard are applicable to and shall be read in conjunction with this method of test. Reference is also made to tests 4.2.1, 4.2.2, and section 5.1 of this Standard.

4.2.3.3

Procedure

- (a) Determine the minimum dry density ($\rho_{d \min}$) and the maximum dry density ($\rho_{d \max}$) by the procedures given in tests 4.2.1 and 4.2.2 respectively. Perform both tests on the same sub-sample with the minimum dry density being determined first because of possible degradation in the maximum dry density test.
- (b) Determine the dry density of soil in place (ρ_d) by one of the procedures specified in section 5.1 of this Standard where relevant. Where none of the procedures in this Standard are relevant, another procedure may be used and shall be fully defined in the test report.

4.2.3.4

Calculations

Calculate the relative density (RD) as a percentage, from the formula:

$$RD = \frac{\rho_{d \max} (\rho_d - \rho_{d \min})}{\rho_d (\rho_{d \max} - \rho_{d \min})} \times 100 \quad \dots\dots\dots\%$$

where ρ_d = dry density of the soil in place (t/m^3)
 $\rho_{d \max}$ = maximum dry density of the soil (t/m^3)
 $\rho_{d \min}$ = minimum dry density of the soil (t/m^3)

4.2.3.5

Reporting of results

4.2.3.5.1

Report the following:

- (a) The date of test
- (b) The relative density to the nearest 5 %
- (c) The minimum dry density (t/m^3) to the nearest 0.02
- (d) The maximum dry density (t/m^3) to the nearest 0.02
- (e) Percentage of oversize material discarded
- (f) The *in situ* density (t/m^3) to the nearest 0.02 and the test method used to determine it
- (g) The maximum size of particle used in the tests for minimum and maximum dry density (mm)
- (h) Whether the optimum double amplitude of vibration was measured or assumed in the test for maximum dry density

Single User PDF Terms & Conditions

You have material which is subject to strict conditions of use. Copyright in this material is owned by the New Zealand Standards Executive. Please read these terms and conditions carefully, as in addition to the usual range of civil remedies available to Standards New Zealand on behalf of the New Zealand Standards Executive for infringement of copyright, under New Zealand law every person who infringes copyright may be liable to a fine of up to \$10,000 for every infringing copy or imprisonment of up to 5 years, or a fine of up to \$150,000 or imprisonment not exceeding 5 years.

You have access to a single-user licence to read this non-revisable Adobe Acrobat PDF file and print out and retain ONE printed copy only.

We retain title and ownership of the copyright in this PDF file and the corresponding permitted printed copy at all times.

Under this license use of both the PDF file and the single permitted printed copy of this PDF file you may make are restricted to you. Under no circumstances are you permitted to save, sell, transfer, or copy this PDF file, the one permitted printed copy of this PDF file, or any part of either of them.

You undertake that you will not modify, adapt, translate, reverse engineer, decompile, disassemble or create derivative works based on any of the downloaded PDF file, nor will you merge it with any other software or document, even for internal use within your organization.

Under no circumstances may this PDF file be placed on a network of any sort without our express permission.

You are solely responsible for the selection of this PDF file and any advice or recommendation given by us about any aspect of this PDF file is intended for guidance only and is followed or acted upon entirely at your own risk.

We are not aware of any inherent risk of viruses in this PDF file at the time that it is accessed. We have exercised due diligence to ensure, so far as practicable, that this file does not contain such viruses.

No warranty of any form is given by us or by any party associated with us with regard to this PDF file, and you accept and acknowledge that we will not be liable in any way to you or any to other person in respect of any loss or damage however caused which may be suffered or incurred or which may arise directly or indirectly through any use of this PDF file.

Regardless of where you were when you received this PDF file you accept and acknowledge that to the fullest extent possible you submit to New Zealand law with regard to this licence and to your use of this PDF file.

Copyright Standards New
Zealand

- (j) Whether the screeding or depth indicator method was used to establish the densified material volume in the test for maximum dry density
- (k) The nominal volume of the mould used in the tests for minimum and maximum dry density (ml)

- (m) The condition of the soil used in the test for maximum dry density e.g. saturated, as received or dry.

4.2.3.5.2

State that the result was obtained in accordance with this Standard Test Method.