

Code of practice for
INDUSTRIAL IDENTIFICATION BY COLOUR,
WORDING, OR OTHER CODING

Pr AA

AMENDMENT No. 2

May 1988

EXPLANATORY NOTE - Amendment No. 2 alters the indication sign for any hazard to safety, to make the safety yellow and black stripe of equal width. Replacement colour stickers for the poster are attached.

To ensure receiving the next amendment to NZS 5807:1980 please complete and return the amendment request form.

DECLARATION

Amendment No. 2 was declared on 27 May 1988 by the Standards Council to be an amendment to NZS 5807:1980 pursuant to the provisions of section 23 of the Standards Act 1965.

(Amendment No. 2, May 1988)

106.7

Indication signs


Delete the entire clause and accompanying figure and **substitute** the following:

106.7

Indication signs

The signs are used:

- (a) To indicate the location of all fire fighting equipment.
'X' stripe safety red, '0.7 X' stripe white,



Single User PDF Terms & Conditions

You have material which is subject to strict conditions of use. Copyright in this material is owned by the New Zealand Standards Executive. Please read these terms and conditions carefully, as in addition to the usual range of civil remedies available to Standards New Zealand on behalf of the New Zealand Standards Executive for infringement of copyright, under New Zealand law every person who infringes copyright may be liable to a fine of up to \$10,000 for every infringing copy or imprisonment of up to 5 years, or a fine of up to \$150,000 or imprisonment not exceeding 5 years.

You have access to a single-user licence to read this non-revisable Adobe Acrobat PDF file and print out and retain ONE printed copy only.

We retain title and ownership of the copyright in this PDF file and the corresponding permitted printed copy at all times.

Under this license use of both the PDF file and the single permitted printed copy of this PDF file you may make are restricted to you. Under no circumstances are you permitted to save, sell, transfer, or copy this PDF file, the one permitted printed copy of this PDF file, or any part of either of them.

You undertake that you will not modify, adapt, translate, reverse engineer, decompile, disassemble or create derivative works based on any of the downloaded PDF file, nor will you merge it with any other software or document, even for internal use within your organization.

Under no circumstances may this PDF file be placed on a network of any sort without our express permission.

You are solely responsible for the selection of this PDF file and any advice or recommendation given by us about any aspect of this PDF file is intended for guidance only and is followed or acted upon entirely at your own risk.


We are not aware of any inherent risk of viruses in this PDF file at the time that it is accessed. We have exercised due diligence to ensure, so far as practicable, that this file does not contain such viruses.

No warranty of any form is given by us or by any party associated with us with regard to this PDF file, and you accept and acknowledge that we will not be liable in any way to you or any to other person in respect of any loss or damage however caused which may be suffered or incurred or which may arise directly or indirectly through any use of this PDF file.

Regardless of where you were when you received this PDF file you accept and acknowledge that to the fullest extent possible you submit to New Zealand law with regard to this licence and to your use of this PDF file.

Copyright Standards New
Zealand

- (b) To indicate any hazard to safety. Stripes of equal width of safety yellow and black.




Note to (a) and (b) - The background colour (that is, red or yellow) to cover at least 50 % of the sign area; 'h' axis may be horizontal or vertical.

(Amendment No. 2, May 1988)


108.1 Signs

In 108.1 (b) SAFETY YELLOW

Delete the sign below;



and **substitute** the following sign;



Yellow shall cover at least 50 % of the area of the sign.

(Amendment No. 2, May 1988)

Fig. 4

Delete the existing figure and **substitute** the following figure:

"Yellow and black stripes to be of equal width with yellow covering at least 50 % of sign area".




Fig 4.

TRIPPING HAZARD Refer clause 108.1(b)(2)

LOW HEAD-ROOM Refer clause 108.1(b)(3)

MOBILE EQUIPMENT Refer clause 108.1(b)4

OBLIGATION TO WEAR SAFETY EQUIPMENT Refer clause 108.1(d)

(Amendment No. 2, May 1988)

POSTER (Inside back flap)

Symbols showing safety colours

SAFETY YELLOW block.

Place attached sticker over relevant figure.

Specific uses of colours and symbols

Fig. 4 Place attached sticker over relevant figure.

(Amendment No. 2, May 1988)